

| Specifications BOX PALLET | | PB-121076-0F00-7 | PB-121076-0E00-7 | PB-121076-0400-7 |
|-------------------------------|----|------------------|------------------|------------------|
| External dimension (W,L,H) | mm | 1000x1200x780 | 1000x1200x780 | 1000x1200x760 |
| Internal dimension (W1,L1,H1) | mm | 920x1120x606 | 920x1120x606 | 920x1120x606 |
| A | mm | 680 | 680 | 680 |
| В | mm | 265 | = | = |
| С | mm | 150 | = | = |
| D | mm | 365 | 365 | = |
| E | mm | 150 | 150 | = |
| F | mm | 880 | 880 | 880 |
| G | mm | 130 | 130 | 110 |
| М | mm | 100 (95) | 100 (95) | = |
| R | mm | | | |
| К | mm | | | |
| Tare Weight (*) | Kg | 37.5 | 35 | 34 |
| Volume | Lt | 615 | 615 | 615 |
| Loading Capacity per Box (**) | Kg | (#)510 at 23°C | (#)510 at 23°C | (#)510 at 23°C |
| Stacking Capacity | Kg | 5000 at 23°C | 5000 at 23°C | 5000 at 23°C |

MAXIMUM STATIC WEIGHT TO BE CARRIED INDIVIDUALLY BY EACH BOX STANDING ON THE FLOOR, $650\ \text{Kg}$

- (*) WEIGHT TOLLERANCE \pm 2%
- DIMENSION TOLLERANCE ± 7mm
- -THE TESTS HAVE BEEN CARRIED OUT AT A TEMPERATURE OF 23°C
- -PRODUCT WERE NOT EXPOSED TO ULTRA VIOLET LIGHT -DRAWINGS & DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE
- -THE PRESENT CHART CANCELS AND REPLACES ALL PREVIOUSLY IUSSED
- (**) FOR LIQUID GOOD THE LOAD RATING DECREASES BY 12%

